


Polymer Systems Technology Limited

UK & Ireland Distributor



© 2011 - Polymer Systems Technology Limited TM
Unit 2. Network 4. Cressex Business Park,
Lincoln Road, High Wycombe, Bucks. HP12 3RF
Phone +44 (0) 1494 446610
Fax: +44 (0) 1494 528611
Web: <http://www.siliconepolymers.co.uk>
Email: sales@silicone-polymers.co.uk



CV6-1144-0

Controlled Volatility RTV Silicone Oxygen Protective Overcoat

Product Profile

Description

- One-Part silicone dispersion with an added UV indicator
- Based on a dimethyl diphenyl silicone copolymer with a broad temperature range
- Provided as an RTV silicone dispersion in VM&P Naphtha

Applications

- For applications requiring extreme low temperature, low outgassing and minimal volatile condensables under extreme operating conditions
- As a protective overcoating for electronic components and atomic oxygen resistance in space applications
- Provides radiation and thermal stress resistance

Typical Properties	Result	Metric Conv.	ASTM	NT-TM
Uncured:				
Color	Clear to opalescent green	-	-	-
Non-Volatile Content	60%	-	D-2288-69	040
Viscosity	300 cP	265 mPas	D-1084, D-2196	001
Work Time	10 min	-	-	008
Cure Time, 50% R.H. @ 25°C				
Tack Free	1 hour	-	C-679	005
Set Up	24 hours	-	-	-
Cure System	Oxime	-	-	-
Full Cure	7 days	-	-	075
Cured: 7 days @ 25°C (77°F), 50% R.H.				
Appearance	Clear to opalescent green	-	D-2090	002
Specific Gravity @ 25°C (77°F)	1.01	-	D-792	003
Refractive Index	1.432	-	D-1747, D-1218	018
Collected Volatile Condensable Material (CVCM)	0.01%	-	E 595	072
Total Mass Loss (TML)	0.33%	-	E 595	072
Operating Temperature Range	-178°F to 500°F	-115°C to 260°C	-	-

Instructions for Use

Thoroughly mix for 5 minutes prior to every use, as the product separates. Apply by spraying, dipping or brushing. Thin with VM&P Naphtha to the appropriate viscosity for spray equipment. Mix with a moisture free solvent in a closed container, preferably with a commercial paint shaker.

Caution: Consult the MSDS for CV6-1144-0 prior to use, as the solvent carrier is hazardous.

Substrate Considerations

Although generally considered to be non-corrosive to most substrates, the oxime cure system may cause discoloration in the presence of copper or copper alloys.

Note: Some bonding applications may require the use of a primer. NuSil Technology SP-120 silicone primer is recommended.

Packaging

100 Grams
 1 Pint (400 g)

Warranty

6 Months

Warnings About Product Safety

NuSil Technology believes that the information and data contained herein for accurate and reliable. However, the user is responsible to determine the material's suitability and safety of use. NuSil Technology cannot know each application's specific requirements and hereby notifies the user that it has not tested or determined this material's suitability or safety for use in any application. The user is responsible to adequately test and determine the safety and suitability for their application and NuSil Technology makes no warranty concerning fitness for any use or purpose. NuSil Technology has completed no testing to establish safety of use in any medical application.

NuSil Technology has tested this material only to determine if the product meets the applicable specifications. (Please contact NuSil Technology for assistance and recommendations when establishing specifications.) When considering the use of NuSil Technology products in a particular application, review the latest Material Safety Data Sheet and contact NuSil Technology with any questions about product safety information.

Do not use any chemical in a food, drug, cosmetic, or medical application or process until having determined the safety and legality of the use. The user is responsible to meet the requirements of the U.S. Food and Drug Administration (FDA) and any other regulatory agencies. Before handling any other materials mentioned in the text, obtain available product safety information and take the necessary steps to ensure safety of use.

Specifications

Do not use the typical properties shown in this technical profile as a basis for preparing specifications. Please contact NuSil Technology for assistance and recommendations in establishing particular specifications.

Patent Warning

NuSil Technology disclaims any expressed or implied warranty against the infringement of any patent. NuSil Technology does not warrant the use or sale of the products described herein will not infringe the claims of any United States' or other country's patents covering the product itself, its use in combination with other products or its use in the operation of any process.

Warranty Information

NuSil Technology's warranty period is 6 months from the date of shipment when stored below 40°C in original unopened containers. Unless NuSil Technology provides a specific written warranty of fitness for a particular use, NuSil Technology's sole warranty is that the product will meet NuSil Technology's then current specification. NuSil Technology specifically disclaims any other expressed or implied warranty, including warranties of merchantability and fitness for use. The exclusive remedy and NuSil Technology's sole liability for breach of warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. NuSil Technology expressly disclaims any liability for incidental or consequential damages.