


S-7200

Variable viscosity silicone fluid

DESCRIPTION



- A clear trimethyl endblocked polysiloxane fluid
- Available in viscosities up to 7 million centipoise, and higher viscosities on a special order basis
- Use of a proprietary catalyst during polymerization offers improved thermal stability

APPLICATION

- For maximum vibration control and damping in dash pots for time delay relays, pulsation dampers and meter movements
- Use as the working media in fluid clutch and fluid drive systems in the aerospace and automotive industry
- Consider for use as a lubricant, coating, release agent or performance additive
- For applications requiring an operating temperature range of -40°C to 200°C (-40°F to 392°F)

PROPERTIES

Typical Properties	Average Result	Metric Conv.	Standard	NT-TM
Appearance	Water Clear	-	ASTM D2090	002
Specific Gravity	1	-	ASTM D792	003
Refractive Index	1.403	-	ASTM D1747, D1218	018
Volatility	2% max	-	ASTM D792	004
Acid Number	0.01	-	ASTM D974	094
Particulate Matter, Screen Mesh Passed	325	-	-	060
Flash Point (open cup)	600°F	315°C	-	-
Dielectric Strength	400 volts/mil	15.7 kV/mm	ASTM D149	-
Dielectric Constant at 100 Khz	2.77	-	ASTM D924	-

Typical Properties	Average Result	Metric Conv.	Standard	NT-TM
Volume Resistivity	1×10^{15}	-	ASTM D257	040
Vapor Pressure at 200°C (392°F)	1×10^{-2}	-	-	-

SPECIFICATIONS

Do not use the properties shown in this technical profile as a basis for preparing specifications. Please [contact](#) NuSil Technology for assistance and recommendations in establishing particular specifications.

WARRANTY INFORMATION

The warranty period provided by NuSil Technology LLC (hereinafter "NuSil Technology") is 12 months from the date of shipment when stored below 40°C in original unopened containers. Unless NuSil Technology provides a specific written warranty of fitness for a particular use, NuSil Technology's sole warranty is that the product will meet NuSil Technology's then current specification. NuSil Technology specifically disclaims all other expressed or implied warranties, including, but not limited to, warranties of merchantability and fitness for use. The exclusive remedy and NuSil Technology's sole liability for breach of warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. NuSil Technology expressly disclaims any liability for incidental or consequential damages.

WARNINGS ABOUT PRODUCT SAFETY

NuSil Technology believes, to the best of its knowledge, that the information and data contained herein are accurate and reliable. The user is responsible to determine the material's suitability and safety of use. NuSil Technology cannot know each application's specific requirements and hereby notifies the user that it has not tested or determined this material's suitability or safety for use in any application. The user is responsible to adequately test and determine the safety and suitability for their application and NuSil Technology makes no warranty concerning fitness for any use or purpose. NuSil Technology has completed no testing to establish safety of use in any medical application.

Packaging

1 Pint (455 g)
1 Gallon (3.64 kg)
5 Gallon (18.2 kg)

Warranty

12 Months

NuSil Technology has tested this material only to determine if the product meets the applicable specifications. (Please [contact](#) NuSil Technology for assistance and recommendations when establishing specifications.) When considering the use of NuSil Technology products in a particular application, review the latest Material Safety Data Sheet and [contact](#) NuSil Technology with any questions about product safety information.

Do not use any chemical in a food, drug, cosmetic, or medical application or process until having determined the safety and legality of the use. The user is responsible to meet the requirements of the U.S. Food and Drug Administration (FDA) and any other regulatory agencies. Before handling any other materials mentioned in the text, the user is advised to obtain available product safety information and take the necessary steps to ensure safety of use.

PATENT / INTELLECTUAL PROPERTY WARNING

NuSil Technology disclaims any expressed or implied warranty against the infringement of any domestic or international patent/intellectual property right. NuSil Technology does not warrant the use or sale of the products described herein will not infringe the claims of any domestic or international patent/intellectual property right covering the product itself, its use in combination with other products, or its use in the operation of any process.



Polymer Systems *Technology Limited*

Silicone Sales & Services UK - Ireland - Benelux

© 2020 - **Polymer Systems Technology Limited™**

Unit 2. Network 4. Cressex Business Park,
Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: <https://www.silicone-polymers.com>

email: sales@silicone-polymers.co.uk

